


## PRODUCT DATA SHEET

## Stair Nosings Appular Carborundum Recessed

- Anodised aluminium with carborundum insert.
- Comprehensive colour range of anti-slip silicon carbide inserts.
- Concealed screw & glue fix for clean look.
- Also available as an Instant Adhesive, no drilling required
- Complies to AS/NZS 1428.1-2009.





| Insert Colours | Clear Anodised | Black Anodised | Brass Anodised | Luminance Contrast          |
|----------------|----------------|----------------|----------------|-----------------------------|
| Black          | SN-APGR-C/BLK  | SN-APGR-BL/BLK | SN-APGR-BR/BLK | LRV: Dry 2.959, Wet 1.972   |
| Grey           | SN-APGR-C/GRY  | SN-APGR-BL/GRY | SN-APGR-BR/GRY | LRV: Dry 15.474, Wet 15.475 |
| Yellow         | SN-APGR-C/YLW  | SN-APGR-BL/YLW | SN-APGR-BR/YLW | LRV: Dry 74.151, Wet 73.081 |
| White          | SN-APGR-C/WHI  | SN-APGR-BL/WHI | SN-APGR-BR/WHI | LRV: Dry 40.717, Wet 40.070 |

|             | -  |
|-------------|--|
| Slip Rating | P5   |
|             | ALUMINIUM COLOURS                            |
| Colours     |  |
|             | CLEAR ANODISED BLACK ANODISED BRASS ANODISED |
|             | INSERT COLOURS                               |
|             |  |
|             | BLACK GREY YELLOW WHITE                      |
|             |  |

58mm x 10mm x 4.8mm Lengths: 4.1m

Applications

Education Institutions, Industrial Applications, Office Areas, Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.

Size

1800 621 103

P

- sales@sterlingsupplies.com.au
- www.sterlingsupplies.com.au

