



STERLING
SUPPLIES

PRODUCT DATA SHEET

Individual Tactiles


Duratac® Stainless Steel Directional Bars Carborundum Top

- High Grade 316 Stainless Steel Bar.
- 3 stems for easy installation.
- Excellent durability and virtually no maintenance.
- Carborundum face for excellent slip resistance.
- Suitable for interior and exterior applications.
- Complies to AS/NZS 1428.4.1-2009.
- 44 units per square meter.



Specifications

Code	TGSI-DGT
Size	290mm Long x 35mm Wide x 4.5mm High x 13mm Stem
Slip Rating	P5



Applications	Education Institutions, Industrial Applications, Office Areas, Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.
--------------	--

Luminance Contrast	Dry 3.42, Wet 40.07
--------------------	---------------------

Required Minimum Contrast	60%
---------------------------	-----

Suitable Substrates	Natural Stone (Granite, Marble Sandstone, Slate, Blue Stone, Basalt & more.) Engineering Stone (Caesar Stone, Quantum Stone & more.) Concrete. Timber/Rubber Vinyl Flooring. Ceramic.
---------------------	---

P 1800 621 103

E sales@sterlingsupplies.com.au

W www.sterlingsupplies.com.au

