




**STERLING**  
SUPPLIES

## PRODUCT DATA SHEET

Individual Tactiles

### Duratac® Polymeric Individual Tactiles

- High grade UV stable polymer.
- 28mm stem.
- Available in 5 colours.
- Excellent durability and virtually no maintenance.
- Textured face for greater slip resistance.
- Complies to AS/NZS 1428.4.1-2009.
- Easy installation by drilling 8mm hole and tap with soft faced hammer into hole.
- 400 units per square meter.



Colours	Code	Size	Specifications
Black - LRV: Dry 3.71, Wet 2.47	TGSI-P/BLK	35.0mm diameter x 5.0mm high x 24.0mm stem	Slip Rating: P4 Required Minimum Contrast 45% SUITABLE SUBSTRATES Natural Stone (Granite, Marble Sandstone, Slate, Blue Stone, Basalt & more.) Engineering Stone (Caesar Stone, Quantum Stone & more.) Concrete, Asphalt. Timber/Rubber Vinyl Flooring.Ceramic.
Blue - LRV: Dry 10.86, Wet 10.28	TGSI-P/BLU		
Grey - LRV: Dry 14.32, Wet 14.05	TGSI-P/GRY		
White - LRV: Dry 91.88, Wet 91.80	TGSI-P/WHI		
Yellow - LRV: Dry 48.74, Wet 49.03	TGSI-P/YLW		

#### Applications

Education Institutions, Industrial Applications, Office Areas,  
Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.

