

PRODUCT DATA SHEET

Car Park Safety In Ground Bollard

- Solid and attractive surface mounted bollard.
- Available in 316 stainless steel or yellow powder coated finish.
- For areas which require pedestrian and asset protection whilst meeting architectural needs. Suits a variety of situations including shopping centres, car parks and building entrances. Ideal choice for locations near salt water.
- Concrete into a footing for maximum strength.

900/1300 Ground Level 90/140



nab

| Codes (Yellow) | Codes (Stainless Steel) | Dimensions | Size |
|----------------|-------------------------|---------------|--------|
| 90BGBOLL/YLW | 90BGBOLL/SS | 90 x 1200 mm | 90 mm |
| 140BGBOLL/YLW | 140BGBOLL/SS | 140 x 1600 mm | 140 mm |
| 165BGBOLL/YLW | 165BGBOLL/SS | 165 x 1600 mm | 165 mm |

Installation Note Locate Bollard in preferred location. Please bear in mind of Vehicular access. In some instances there may be regulations on where bollards are to be installed e.g Disabled Shared Access, around Fire Equipment. Bollards can either be concreted into a footing. Please request footing detail. If area is already concreted, Core Drilling is required and then pour Structual Grout around the bollard to ensure rigidity. Please request Core Drill Hole size.

Applications:

Educational Facilities, Retail Centres, Airports, Residential Car Parks, Other Public Car Parks, Industrial Applications.

P 1800 621 103

E sales@sterlingsupplies.com.au

www.sterlingsupplies.com.au