


## PRODUCT DATA SHEET

## Stair Nosings Transola

- High slip resistant fibreglass nosing.
- Surface mounted with extreme slip rating, ideal for industrial environments.
- Resistant to most chemicals.
- Can be adhered or screwed/riveted to surface.
- · Ideal for external use.
- Also available as an Instant Adhesive, no drilling required.
- Complies to AS/NZS 1428.1-2009.





5mm x Length	SN-TR10/BLK SN-TR10/YLW SN-TR30/BLK SN-TR30/YLW C10mm x 3mm 30mm x 3mm s: 4.1 m	LRV: Dry 7.6, Wet 6.6 LRV: Dry 36.8, Wet 39.5
Size 75mm x 5mm x Length	SN-TR30/BLK SN-TR30/YLW 10mm x 3mm 30mm x 3mm	LRV: Dry 36.8, Wet 39.5
5mm x Length	SN-TR30/YLW x 10mm x 3mm 30mm x 3mm	
5mm x Length	x 10mm x 3mm 30mm x 3mm	
5mm x Length	30mm x 3mm	
Slip Rating P5		
Colours FIBREGLA	BLACK (Available on request)	
	on Institutions, Industrial Application hments, Shopping Centres, Sports F	ons, Office Areas, Restaurants/Eating Facilities.

- P 1800 621 103
- **E** sales@sterlingsupplies.com.au
- www.sterlingsupplies.com.au