



PRODUCT DATA SHEET

Dry Area Mat Link Mat

- A durable, rubber, interlocking mat ideal for long lengths or to cover large areas.
- Available in solid top or with holes.
- Rubber compound with good anti-fatigue properties.
- Tapered ramps and corners.
- Interlocking ramps come with both male and female interlocking sections to suit mat.



Code	Size & Thickness	Installation Note
909S9090	900 x 900 mm	Ensure the area is clean and all vacuumed beforehand. Start by laying the first mat in the position that you require with the male lugs facing towards their joining tile. See diagram - Continue to lay in this fashion to cover the area required. For correct application of the ramps ensure you have male lugs all on one side of the mat, then fit the female or male ramps accordingly. Note - The ramps are manufactured with corner pieces moulded on each end of the ramps, these will need to be cut off prior to laying where they aren't required.
909H9090	900 x 900 mm	
909RM90BK	900 mm ramp	
909RM90YLW	900 mm ramp	
909RF90BLK	Corners: 160mm x 160mm	
909RF90YLW	Mats: 900mm x 900mm	
	Ramps: 60mm x 900mm	
	Thickness: 16 mm	

Colours



BLACK
(no holes)



BLACK
(with holes)



BLACK RAMP



YELLOW RAMP

Applications Industrial Applications

P 1800 621 103

E sales@sterlingsupplies.com.au

W www.sterlingsupplies.com.au

