



STERLING
SUPPLIES

PRODUCT DATA SHEET

Low Traffic

Décor Plush

Classic commercial matting with a plush polypropylene surface. Décor Plush has multiple uses: Entry matting and, can be used as a chair mat on hard surfaces – slows chair movement, or can be used as an insulator on cold concrete floors

- Heavy duty polypropylene plush pile fibre construction dries quickly.
- Slip resistant vinyl backing with 25mm borders.
- Light weight and easy to clean.
- Stain and fade resistant.
- Available with non trip edging



Code	Size & Thickness	Installation Note
5126090	600 x 900mm	Ensure the recess is clean and free of debris. Cut the mat to the size of the recess using a trimming knife, such as a Stanley knife (or similar). Use Sikabond 105 Contact Fix and spread evenly over both surfaces either by sprayer or trowel. Place the mat on top of the adhesive and use a vinyl roller (or similar) to apply even pressure over the surface of the mat. Ensure the mat is trimmed correctly to the area to prevent tripping hazards.
51290150	900 x 1500mm	
512120180	1200 x 1800mm	
51290C	900mm wide runner	
512120C	1200mm wide runner	
512180C	1800mm wide runner	
51290C	900mm x 18.2m roll	
512120C	1200mm x 18.2m roll	
512180C	1800mm x 18.2m roll	
	Custom sizes available	
	Thickness: 7 mm	

Colours



DARK GREY

Applications Residential Buildings, Light Commercial Buildings.

P 1800 621 103

E sales@sterlingsupplies.com.au

W www.sterlingsupplies.com.au

