



STERLING SUPPLIES

PRODUCT DATA SHEET

High Traffic

Entrymaster® Classic

Entrymaster® Classic has proven itself time and again as an excellent performing polypropylene entrance mat. It has a rubber-reinforced profile to prevent the pile crushing in even the highest traffic areas and features a 'Water Dam' edge which retains dirt and water.

- Raised pattern will not flatten.
- Excellent dirt and water retention.
- Cleated back minimises movement on most surfaces, especially carpet.
- Moulded rubber edge is tear, curl and damage resistant.
- Easily cleaned by sweeping, vacuuming or hosing.
- Durable polypropylene will not fade, rot or stain - dries quickly.
- Anti-static, safe for use in sensitive areas. Rating: 1.2KV.



Code	Size & Thickness	Specifications	Installation Note
2006090	580 x 870 mm	Slip Rating: P5 Flammability: CHF 1.1, Smoke Value 766	Ensure the recess is clean and free of debris. Cut the mat to the size of the recess using a trimming knife, such as a Stanley knife (or similar). Use Sikabond 105 Contact Fix and spread evenly over both surfaces either by sprayer or trowel. Place the mat on top of the adhesive and use a vinyl roller (or similar) to apply even pressure over the surface of the mat. Ensure the mat is trimmed correctly to the area to prevent tripping hazards.
20090150	860 x 1450 mm		
200120180	1140 x 1760 mm		
200180240	1800 x 2400 mm		
20090C	860m wide runner		
200120C	1140mm wide runner		
200180C	1800mm wide runner		
20090300	860mm x 3.0m roll		
20090C	860mm x 6.0m roll		
200120C	1140mm x 6.0m roll		
200180C	1800mm x 6.0m roll		
	Custom sizes available		
	Thickness: 9 mm		

Colours



CHARCOAL

Applications Educational Institutions, Industrial Applications, Office Areas
Restaurants/Eating Establishments, Shopping Centres, Sports Facilities

P 1800 621 103

E sales@sterlingsupplies.com.au

W www.sterlingsupplies.com.au

