



STERLING
SUPPLIES

PRODUCT DATA SHEET

High Traffic

Trapper Entrance Tile

Modular carpet tile entrance matting for quick easy effective entrance matting that easily incorporates with carpet tiles or other floor covering installations.

Coarse fibres give extreme scrubbing action to remove dirt and prevent it tracking into the building.

- Easy to install, no recess required, simply butt up to other floor coverings.
- Heavy duty performance, suitable for high traffic areas.
- Slip resistant, mitigates slips and falls.
- Solution dyed Nylon 6.
- Saves on cleaning costs, easy to install and clean.
- Dimensionally stable, will not cup or curl, shrink or grow.
- Meets Australian flammability requirements.



Specifications

Code	TET5050/CHA
Size	500mm x 500mm tiles Thickness: 7 mm
Slip Rating	P4
Flammability	CHF 3.4 , Smoke Value 242



7.0

Colours



GRAPHITE

Applications

Educational Institutions, Industrial Applications, Office Areas, Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.

Installation note

Fitting to a Recess. Ensure the recess is clean and free of debris. Use approved Glue for use with carpet Tiles and apply by manufacturer's instructions. Starting form one corner lay the tiles either in a linear fashion or rotate it See diagram: Cut the tiles to suit the recess as you lay them, use a vinyl roller (or similar) to apply even pressure over the surface to ensure they stick. Laying with other Carpet Tiles.

P 1800 621 103

E sales@sterlingsupplies.com.au

W www.sterlingsupplies.com.au

