



STERLING
SUPPLIES

PRODUCT DATA SHEET

Tactile Tiles / Plates

Duratac® Eco Directional Tiles

Our Duratac® Eco Directional Tiles are made to comply with industry standards set out in AS/NZS 1428.4 and are designed with a high P5 slip rating suitable for almost any application.

This tactile has been cleverly designed using an ultra UV stabilised resin guaranteed to last a minimum of 5 years without fading and a specially developed reinforced embedded fiberglass resulting in a super strong product that will be durable in even the most heaviest pedestrian traffic areas. Installed using raw plugs and stainless steel screws in conjunction with Icons Extreme Hold Adhesive.

- Super strong product, durable in heaviest pedestrian traffic areas.
- High slip rating.
- Ideal for exterior applications such as footpaths and pedestrian crossings.
- Complies to AS/NZS 1428.4.1: 2021.
- 6 units per square meter.
- Supplied with 8 fixings per tile.



Colours	Code	Size	Specifications
Black - LRV: Dry 4.27, Wet 3.92	TGSI-FD3060/BLK	600mm Long x 300mm Wide x 5mm High	Slip Rating: P5 Required Minimum Contrast 30% SUITABLE SUBSTRATES Natural Stone (Granite, Marble Sandstone, Slate, Blue Stone, Basalt & more) Engineering Stone (Caesar Stone, Quantum Stone & more) Concrete, Asphalt (requires priming.) Timber/Rubber Vinyl Flooring. Ceramic.
White - LRV: Dry 72.28, Wet 77.47	TGSI-FD3060/WHI		
Yellow - LRV: Dry 52.87, Wet 52.42	TGSI-FD3060/YLW		

Applications

Education Institutions, Industrial Applications, Office Areas, Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.

