




PRODUCT DATA SHEET

Individual Tactiles

Duratac® Polymeric Individual Tactiles

- High grade UV stable polymer.
- 28mm stem.
- Available in 5 colours.
- Excellent durability and virtually no maintenance.
- Textured face for greater slip resistance.
- Complies to AS/NZS 1428.4.1:2021.
- Easy installation by drilling 8mm hole and tap with soft faced hammer into hole.
- 400 units per square meter.



Colours	Code	Size	Specifications
Black - LRV: Dry 3.280, Wet 2.475	TGSI-P/BLK	35.0mm diameter x 5.0mm high x 24.0mm stem	Slip Rating: P4 Required Minimum Contrast 45% SUITABLE SUBSTRATES Natural Stone (Granite, Marble Sandstone, Slate, Blue Stone, Basalt & more.) Engineering Stone (Caesar Stone, Quantum Stone & more.) Concrete, Asphalt. Timber/Rubber Vinyl Flooring.Ceramic.
Blue - LRV: Dry 10.826, Wet 0.287	TGSI-P/BLU		
Grey - LRV: Dry 14.320, Wet 14.045	TGSI-P/GRY		
White - LRV: Dry 91.879, Wet 91.801	TGSI-P/WHI		
Yellow -LRV: Dry 48.218, Wet 47.105	TGSI-P/YLW		

Applications

Education Institutions, Industrial Applications, Office Areas,
Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.

