



PRODUCT DATA SHEET

Low Traffic

Black Coir matting

Coir Matting is a coconut fibre mat that absorbs moisture and scrapes dirt. This entrance mat is ideal for use in light commercial areas where there is low traffic. It prevents spread of moisture and dirt, resulting in lower maintenance and cleaning costs for all floors. The PVC backing also protects the floor beneath against tracked-in moisture.

We use specially selected coconut fibre yarns and dye them which gives the Coir a deep colour. This authentic and robust product is the result of decades of experience and craftsmanship. Like other natural products, there may be inconsistencies in colour and exposure to the sun may cause fading over time. This should be considered in your selection.

- Naturally attractive matting suitable for a variety of applications.
- Coconut fibre matting with vinyl backing for strength and dirt retention.
- Thickness to suit entrance mat recess depth.
- Can be cut to any size and used as a loose lay mat.
- Ideal for indoor and sheltered outdoor use.



Specifications

Code	505017C
Size	17 mm thick (cut to size) 17 mm x 11.2 m x 2.0 m Thickness: 17 mm



Specifications	Does Not Comply with Australian Flammability Standards.
----------------	---------------------------------------------------------

Colours



BLACK

Applications	Educational Institutions, Industrial Applications, Office Areas.
--------------	------------------------------------------------------------------

Installation note

Ensure the recess is clean and free of debris. Cut the mat to the size of the recess using a trimming knife, such as a Stanley knife (or similar). Use Sikabond 105 Contact Fix and spread evenly over both surfaces either by sprayer or trowel. Place the mat on top of the adhesive and use a vinyl roller (or similar) to apply even pressure over the surface of the mat. Ensure the mat is trimmed correctly to the area to prevent tripping hazards.

