



STERLING
SUPPLIES

PRODUCT DATA SHEET

Tactile Tiles / Plates

Duratac® Stainless Steel Plate with Carborundum Insert

- High grade 8mm stainless steel integrated tactile plate with silicon carbide inserts
- Excellent durability and virtually no maintenance
- Bevelled edges to minimize tripping hazards
- Each indicator is plug welded
- Suitable for interior and exterior applications, ideal for surface mount
- 6 units per square meter
- Complies to AS/NZS 1428.4.1-2009 & AS 4586



Specifications

Code	TGSI – 3060/SSGT
Size	600mm Long x 300mm Wide x 5mm High
Slip Rating	P5



Applications	Education Institutions, Industrial Applications, Office Areas, Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.
--------------	--

Luminance Contrast	LRV - Dry 4.69, Wet 4.45
--------------------	--------------------------

Required Minimum Contrast	60%
---------------------------	-----

Suitable Substrates	Natural Stone (Granite, Marble Sandstone, Slate, Blue Stone, Basalt & more.) Engineering Stone (Caesar Stone, Quantum Stone & more.) Concrete, Asphalt (requires priming). Timber/Rubber Vinyl Flooring. Ceramic
---------------------	--

