



PRODUCT DATA SHEET

Tactile Tiles / Plates



Duratac® Stainless Steel Plate with Carborundum Insert

- High grade 8mm stainless steel integrated tactile plate with silicon carbide inserts
- Excellent durability and virtually no maintenance
- Bevelled edges to minimize tripping hazards
- Each indicator is plug welded
- Suitable for interior and exterior applications, ideal for surface mount
- 6 units per square meter
- Complies to AS/NZS 1428.4.1-2009 & AS 4586



Specifications

| | |
|--------------------|-------------------------------------|
| Code | TGSI-3060/SSGT |
| Size | 600 mm Long x 300mm Wide x 5mm High |
| Slip Rating | P5 |



Applications Education Institutions, Industrial Applications, Office Areas, Restaurants/Eating Establishments, Shopping Centres, Sports Facilities.

Luminance Contrast LRV: Dry 4.69 , Wet 4.45

Required Minimum Contrast 60%

Suitable Substrates Natural Stone (Granite, Marble Sandstone, Slate, Blue Stone, Basalt & more.)
Engineering Stone (Caesar Stone, Quantum Stone & more.)
Concrete, Asphalt (required priming)
Timber/Rubber Vinyl Flooring.
Ceramic.

P 1 800 621 103

E sales@sterlingsupplies.com.au

W www.sterlingsupplies.com.au

